## **REGRESSED CONICAL ADJUSTABLE ACCENT LIGHTS**

Quad lamps, solid state light engine, recessed accent lights with (4) 5"(127mm) round trim, round aperture and optional glass diffuser. Accent and downlighting in low to medium ceiling heights typically found in residential, commercial and retail applications. Suitable for new construction.

## SPECIFICATIONS

#### HOUSING

Precision die-formed heavy gauge aluminum

#### MOUNTING

Recessed in architectural ceiling

#### ELECTRICAL

· Integral dimmable electronic driver with internal short circuit protection

#### LAMP

• (4) Citizen LED supplied with fixture

#### SOCKET

Precision die-formed aluminum yoke with CNC machined lampholder assembly

#### LENS

- Interchangeable reflector provides multiple beam patterns
- · Optional borosilicate lenses available for lampholder and aperture

### TRIM

· Flanged, one piece die-cast aluminum 2 shallow conical shields and round aperture

### FINISH

- Black powder paint housing
- · Aperture trim available in white as standard

#### LABELS


• 🚯 , US tested to UL standards 1598, Damp location, Wet with ST trim

22" (559 MM) -20 ½" (521 MM)

13 3/4" (349 MM)


814


(210 MM)



# 1001Q-4MDL-LEDZ-UH

JOB:	
SPECIFIER:	
TYPE:	
QUANTITY:	
SIGNATURE:	





## **ORDERING INFORMATION**

5 1/2

(140 MM)

1" (25 MM) MAX

CEILING

1001Q-4MDL-LEDZ-UH	TRIM	SOURCE / DRIVER	BEAMSPREAD	TRIM FINISH	APERTURE LENS
		1		P14	
Quad Lamp Universal Housing 9 = 90+CRI 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	FT=Flanged Trim ST=Shower Trim* *Req. Aperture Lens	CZ14=120-277v, 14W 1100Im CZ20=120-277v, 20W 1650Im S1 =0-10V dimming, 1%, 120-277v T1 =TRIAC/ELV 2-wire, 3% 120v (Lead/Trail Edge) E1 =EldoLED 0-10V Logarithmic Dim, 0.1%, 120-277v E2 =EldoLED DALI, 0.1%, 120-277v E3 =EldoLED 0-10V Linear Dim, 0.1%, 120-277v L2 =Ltm Hi-lume 1% 2-wr LED driver (120v fwrd phase) L3 =Lutron Hi-lume 1% EcoSys LED driver, 1%, 120-277v, Soft-on, Fade-to-Black	<b>15</b> = 15 Degrees <b>24</b> = 24 Degrees <b>38</b> = 38 Degrees <b>60</b> = 60 Degrees	P14 = White	91A = Solite 93A = Frosted



Patent Pending. These specifications subject to change without notice.

#### www.specialtylightingindustries.com 1306 Doris Avenue, Ocean, NJ 07712 USA 800.462.7812 732.517.0800 FAX:732.517.0971 11/17