REGRESSED CONICAL ADJUSTABLE ACCENT LIGHTS

1016-3MDL-LEDZ-PH

Multi lamp, solid state light engine, recessed accent lights with (3) 4"(102mm) trim, round aperture and optional glass diffuser. Accent and downlighting in low to medium ceiling heights typically found in residential, commercial and retail applications. Suitable for new construction.

SPECIFICATIONS

HOUSING

· Precision die-formed heavy gauge aluminum

MOUNTING

· Install from below in sheetrock ceiling

ELECTRICAL

· Integral dimmable electronic driver with internal short circuit protection

LAMP

· (3) Citizen LED supplied with fixture

SOCKET

· Precision die-formed aluminum yoke with CNC machined lampholder assembly

LENS

- · Interchangeable reflector provides multiple beam patterns
- · Optional borosilicate lenses available for lampholder and aperture

IKIIV


· Flangeless, one piece die-cast aluminum 3 shallow conical shields and round aperture


FINISH


- · Black powder paint housing
- · Aperture trim available in white as standard

LABELS

• 🕦 , US tested to UL standards 1598, Damp location







ORDERING INFORMATION

1016-3MDL-LEDZ-PH	TRIM	SOURCE / DRIVER	BEAMSPREAD	TRIM FINISH	APERTURE LENS
	ZT	1		P14	
Multi Lamp Plaster Housing 9 = 90+CRI 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	ZT =Zero Trim	CZ14=120-277v, 14W 1100lm CZ20=120-277v, 20W 1650lm S1=0-10V dimming, 1%, 120-277v T1=TRIAC/ELV 2-wire, 3% 120v (Lead/Trail Edge) E1=EldoLED 0-10V Logarithmic Dim, 0.1%, 120-277v E2=EldoLED DALI, 0.1%, 120-277v E3=EldoLED DALI, 0.1%, 120-277v L2=Ltm Hi-lume 1% 2-wr LED driver (120v fwrd phs) L3=Lutron Hi-lume 1% 3-wire/EcoSystem, 120-277v LTB=Lutron Hi-lume 1% EcoSys LED driver, 1%, 120-277v. Soft-on. Fade-to-Black	15 = 15 Degrees 24 = 24 Degrees 38 = 38 Degrees 60 = 60 Degrees	P14 = White	Blank = None 91A = Solite 93A = Frosted



Patent Pending. These specifications subject to change without notice.