SPECIFICATIONS

HOUSING - Heavy gauge extruded aluminum/brass (material of corrosion resistant alloy.) Welded aluminum/brass end plate, no visible seam,

REFLECTOR - Semi-specular, low iridescence. aluminum.

ELECTRICAL - T5, integral electronic ballast. 120/277v (dimmable available.)

SOCKET - G5, 600v, 120w, with rotor for secure lamp retention.

TYPE: JOB:

MOUNTING - Cantilevered, see mounting options next page.


LABELS - UL, CUL, - Dry Location.

LAMP - T-5 - by others.

FINISH - Powder paint, brass, or aluminum. Lacquer top coat. RAL colors standard, consult factory for custom finishes.

APPLICATIONS

Art lighting designed to evenly illuminate standard size works of art (up to 4' tall.) Can also be used as indirect ceiling/cove lighting.



ORDERING INFORMATION

FIXTURE	LAMP	LENGTH	PROJECTION	MOUNTING OPTIONS
#204FL				
Picture light	14T5 = 14W 21T5 = 21W 28T5 = 28W 24HOT5 = 24W HO 39HOT5 = 39W HO 54HOT5 = 54W HO	specify exact length	specify exact length	A = Cord & plug B = J-box C = Through panel D = Desk/lectern E = End swivel
		FINISH	•	•

WHT = White



SPECIALTY LIGHTING INDUSTRIES, INC.

PA = Polished aluminum BLK = Black SA = Satin aluminum XXXX = RAL # CST = Custom paint (must supply chip) PB = Polished brass SB = Satin brass

AB = Antique brass

www.specialtylightingindustries.com