

Fully recessed extruded aluminum accent light housing available in a variety of aperture sizes to accommodate a large range of linear and point sources. Three circuit wireway provides power for a wide array of lighting elements that can be located anywhere along the length of the housing. Optional fourth circuit for indirect ambient light. Available in flanged and flangeless trims and with optional aperture lenses.

Useful in applications such as museum, retail and residential environments; the system is totally flexible with lighting elements that may be easily changed in the field to respond to varying architectural conditions. The 3000 series is a tool that allows the designer to create a unified design that is easier to understand and results in a space that is more comfortable to inhabit.

### COMPATIBILITY GUIDE

Model	Aperture	Dimensions W x H	Lamp
3104	4"	14 1/4" x 9 1/2"	ALR12, ALR18, MR16, MR16MH LED, T3, T5, T8
3125	5"	15 1/4" x 12"	All of the above plus PAR20, PAR20MH, PAR30 LED, T3, T5, T8
3125	5"	15 1/4" x 12"	All of the above plus AR111, PAR30MH LED, T3, T5, T8
			All of the above plus PAR38, PAR38MH LED, T3, T5, T8

### TECHNICAL SHEET REFERENCE

Use the model, lamp and housing code to find the technical sheet for the exact configuration you need.  
i.e. 3074-PH-FF

Find technical sheets at [www.specialtylightingindustries.com](http://www.specialtylightingindustries.com)

Model	Housing	Trim
3074	PH	FF
3094	UH	
3095		
3117		

### RELATED PRODUCTS

Elements	3200, 3300, 3400
Down light	4044
Accent light	1044
Wall washer	1240

### ACCESSORIES

Aperture lenses  
Mitered corners



