FLAT PINHOLE APERTURE FIXED ACCENT LIGHTS

4000-3MDL-LEDZ-APH

Multiple lamp, solid state light engine, recessed accent lights with (3) 4"(102mm) trim, round aperture and optional glass diffuser. Accent and downlighting in low to medium ceiling heights typically found in residential, commercial and retail applications. Suitable for new or existing construction in sheetrock ceilings.

SPECIFICATIONS

HOUSING

- · Precision die-formed heavy gauge aluminum
- SAirtight construction suitable for direct contact with insulation

MOUNTING

· Install from below in sheetrock ceiling

ELECTRICAL

· Integral dimmable electronic driver with internal short circuit protection

LAMP

• (3) Citizen LED supplied with fixture

SOCKET

· Precision die-formed aluminum yoke with CNC machined lampholder assembly

LENS

- · Interchangeable reflector provides multiple beam patterns
- Optional borosilicate lenses available for lampholder and aperture

TRIM


• Flangeless, one piece die-cast aluminum 3 flat round plates and round aperture


FINISH


- · Black powder paint housing
- · Aperture trim available in white as standard


LABELS


• US tested to UL standards 1598, Damp location, Wet with SZT trim, IC/Airtight, Chicago Plenum











ORDERING INFORMATION

4000-3MDL-LEDZ-APH	TRIM	SOURCE / DRIVER	BEAMSPREAD	TRIM FINISH	APERTURE LENS	ACCESSORIES
		1		P14		
Multi Lamp Airtight Plaster Housing 9 = 90+CRI 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	ZT=Zero Trim SZT= Shower Zero Trim* *Aperture lens required	CZ14 =120-277v, 14W 1100lm CZ20 =120-277v, 20W 1650lm	15 = 15 Degrees 24 = 24 Degrees 38 = 38 Degrees 60 = 60 Degrees	P14 = White	91A = Solite 93A = Frosted	CP=Chicago Plenum
		C1 =0-10V dimming, 1%, 120-277v C2 =TRIAC/ELV 2-wire, 3% 120v (Lead/Trail Edge) E1 =EldoLED 0-10V Logarithmic Dim, 0.1%, 120-277v E2 =EldoLED DALI, 0.1%, 120-277v E3 =EldoLED 0-10V Linear Dim, 0.1%, 120-277v L2 =Lutron Hi-lume 1% 2-wr LED driver (120v forward phase) LTB =Lutron Hi-lume 1% EcoSys LED driver, 1%, 120-277v, Soft-on, Fade-to-Black				

