

SPECIFICATIONS

**HOUSING** - Heavy gauge extruded aluminum  
(material of corrosion resistant alloy.)  
Aluminum end plate.

**REFLECTOR** - Specular, low iridescence, aluminum.

**ELECTRICAL** - T5, T8, integral electronic ballast,  
120/277v (dimmable available.)

**SOCKET** - G-5, 600v, 120w, with rotor for secure  
lamp retention.

**MOUNTING** - Recessed, in floor.

TYPE: \_\_\_\_\_

JOB: \_\_\_\_\_

\_\_\_\_\_

**LABELS** - UL, C-UL -Dry Location.




**LAMP** - T-5, T-8 - by others.

**LENS** - Fresnel, acrylic, and clear Pyrex protective  
cover.

**FINISH** - Powder paint on all surfaces. RAL colors  
standard, consult factory for custom finishes.

APPLICATIONS

Medium profile, recessed  
uplight, intended to  
highlight surface texture in  
brick, stone, stucco, tile,  
textured paint, fabric and  
wood panels.



ORDERING INFORMATION

FIXTURE	LAMP	LENGTH	FINISH	OPTIONS
<b>#609FL</b>				
Recessed linear wall grazing system uplight	<b>14T5</b> = 14w <b>24HOT5</b> = 24w HO <b>21T5</b> = 21w <b>39HOT5</b> = 39w HO <b>28T5</b> = 28w <b>54HOT5</b> = 54w HO  <b>2T8</b> = 2', 17w <b>3T8</b> = 3', 25w <b>4T8</b> = 4', 32w	specify exact length	<b>WHT</b> = White <b>BLK</b> = Black <b>XXXX</b> = RAL # <b>CST</b> = Custom (must supply chip)	<b>BFL2</b> = baffles 2" o.c. <b>BFL4</b> = baffles 4" o.c.



SPECIALTY LIGHTING  
INDUSTRIES, INC.

www.specialtylightingindustries.com

1306 DORIS AVENUE, OCEAN, NJ 07712 USA

800.462.7812

732.517.0800

FAX 732.517.0971