SLICI

Multi-lamp, solid state light engine, recessed linear wall grazer with flangeless housing. Narrow profile wall grazer used in medium ceiling heights to highlight the texture in surfaces such as stucco or brick, illuminate flat surfaces such as venetian plaster, fabric, wood, or general lighting

# **SPECIFICATIONS**

## **HOUSING**

· Aluminum housing with integrated screed edge

## **MOUNTING**

· Recessed in architectural ceiling

## **ELECTRICAL**

- · Integral electronic dimmable driver
- 1, 2, 5 Cell configurations require Remote driver
- · 1724 maximum lumens available

## LAMP

 (10), 80 CRI, 3000K Standard LED - supplied with fixture Consult factory for additional options

## SOCKET

· Circuit board mounted to extruded aluminum heatsink

#### LENS

- Acrylic diffusing lens as standard, narrow and wide beam optics available as standard
- · Consult factory for custom options

#### TRIM


· Flangeless


## **FINISH**

- · Paint on all surfaces in black and white as standard
- Additional colors and RAL palette available
- · Consult factory for custom finishes

## **LABELS**


• ① US tested to UL standards 1598, Damp location, IC Rated







| OUTPUT CHART* |             |  |  |  |
|---------------|-------------|--|--|--|
| WIDE (WD)     | NARROW (NW) |  |  |  |
| 1306 Lm       | 1724 Lm     |  |  |  |
| 24 w          | 24 w        |  |  |  |

\*Based on 10H Configuration







# **ORDERING INFORMATION**

| 888-LED-PH                 | CELLS                       | VOLTAGE                                | DRIVER  | LOUVER                                  | OPTIC                    | APERTURE LENS        |
|----------------------------|-----------------------------|--|---|---|--------------------------|----------------------|
| SM                         |                             |  |   |   |                          |                      |
| BAFFLE TYPE<br>SM = Smooth | 1H*<br>2H*<br>5H*<br>10H    | 120<br>220/240<br>277<br>UNV = 120-277 | 2D = No Dimming<br>3D = TRIAC /ELV**<br>4D = 0-10v Dimming<br>RX = remote | WHT= White<br>BLK= Black<br>CST= Custom | NW = Narrow<br>WD = Wide | 79A= Veiling Acrylic |
|                            | CST *Requires Remote Driver |  | *Consult factory for additional options                                   |   |                          |                      |



U.S. Patent D788,968S

These specifications subject to change without notice.